

# FREIDORA -FRYER



FPT-XXXX

## Higiene y accesibilidad:

Sistema hidráulicos para sus movimientos, sistema limpio y fácilmente regulable.

Estructura con puertas desmontable, permiten el acceso al interior de la máquina fácilmente.

Sinfín helicoidal para la extracción de residuos en el interior de la cámara.

Quemadores industriales para **gasoil o gas** (LP o g. natural), totalmente homologados; en los modelos inferiores también versión eléctrica sistema innovador, **sin resistencias dentro del aceite**

Construida íntegramente en Acero Inoxidable AISI304  
Protección IP 66.

TIEMPO DE PROCESO	TIEMPOS
ARGA PRODUCTO	50 Seg
ADDA BATIDOR	30 Seg
TRURA	175 Seg
CURRIDO	18 Seg
SCARGA	7 Seg
TARDO MARCHA SALIDA FREIDORA	45 Seg
TIEMPO TRABAJO SALIDA FREIDORA	90 Seg



FPT-XXXX

## Hygiene and accessibility:

Moved by hydraulic system, clean and easily adjustable system.  
Structure with removable doors, allows inner of the machine easily.

Helical auger for the extraction of waste inside the chamber.

Industrial burners for **gasoil or gas** (LP or natural gas), fully homologated; in the lower models there are also innovative electric version systems, **without heater elements inside the oil**

Built entirely in Stainless Steel AISI304  
Protection IP 66.

Modelo Model	Dimensiones aprox. Approx. dimensions L x B x H (mm)	Produccion frito aprox. Approx. fried production (Kg/h)	Consumo gasoil aprox. Approx. gasoil consumption (l/h)	Capacidad aceite aprox. Approx. oil capacity (l)	Accesorios Accessories Filtro de aceite Oil filter Nivel de aceite Oil level	
FPT-2100	2100X2100X1100	120/135	24	700	X	X
FPT-1870	1870X1870X1100	100/110	16	550	X	X
FPT-1600	1600x1600x1000	75/80	12	400	-	-
FPT-1400	1400x1400x1000	45/55	8	250	-	-
FPT-1200	1200x1200x1000	35/40	6	200	-	-